

Solver Paints

Head Office:

560 Churchill Road, Kilburn, South Australia 5084

Telephone: (08) 8368 1200 Facsimile: (08) 8368 1222

www.solverpaints.com.au

Solver Paints is the registered trademark
of WP Crowhurst Pty Ltd A.B.N. 65 007 527 371



Revised Jan 2008

PRODUCT INFORMATION

SU-4334-01

SOLVER LINE 4334 - PLASTER GLASS SEALER

DESCRIPTION:

A Super Premium, interior, solvent based sealer for use on unpainted Plaster Glass sheeting. It seals the porous surface to provide one of uniform absorption before overcoating with either water or solvent based finishing systems. Not suitable for alkaline surfaces (Use SOLVER Line 4129 Wall-Sealer).

USE ON:

As a sealer for unpainted Plaster Glass. SOLVER Line 4334 Plaster Glass Sealer is NOT suitable for use over highly alkaline surfaces. Use SOLVER Line 4129 Wall-Sealer over surfaces known to be highly alkaline.

DO NOT use for any purpose other than as specified in our literature.

COVERAGE:

Approximately 9 square metres per litre on smooth surfaces. This equates to a film thickness of 33 microns, not taking into account losses due to method of application.

SURFACE PREPARATION:

All surfaces must be clean, sound and dry. Ensure that any flushing compounds used are completely dry and cured. Make good any surface imperfections with appropriate patching material. Sand lightly and dust off. On previously painted surfaces remove any loose or flaking paint and sand smooth. Spot prime with SOLVER Line 4334 Plaster Glass Sealer.

FUNGUS INFECTED AREAS:

Treat the surface with SOLVER Line 4651 Sterilizing Wall-Wash. If abnormal conditions are expected, SOLVER Line 4651 Anti-Fungus Additive can be added to the paint for extra protection. For normal conditions this addition will not be necessary.

STIRRING:

Mix contents thoroughly with a broad flat paddle reaching to the bottom of the can.

THINNING:

Normally used unthinned. However if necessary thin sparingly with Mineral Turps for brush and roller application. Do not add more than 5%. For spray application thin as required with SOLVER Line 4600 Spraying (Fast) Thinner for normal spraying conditions. In hot, windy conditions thin for spraying with SOLVER Line 4355 Enamel (Slow) Thinner.

APPLICATION:

Apply 1 full even coat by brush, roller or spray. Use a short nap roller (6 mm pile). Use an 11 thou. spray tip. DO NOT apply under cold or very damp conditions or when condensation, dew or frost are likely.

DRYING TIME:

When temperature is around 25°C:-

DRY TO TOUCH: 2 - 4 hours
RECOAT: 16 hours

Under cooler or humid conditions allow longer times.

CLEAN-UP:

Clean up with Mineral Turps. For best care of equipment use SOLVER Line 4331 Brush & Roller Cleaner to complete the clean up.

COLOURS:

White only.

SIZES:

10 litre, 4 litre.

CAUTION:

Flammable. Keep away from heat and open flame. Keep closed when not in use.

PROVIDE ADEQUATE VENTILATION DURING USE.

FOR FURTHER SAFETY INFORMATION REFER TO MATERIAL SAFETY DATA SHEET AND ALSO PRODUCT INFORMATION SHEET SS-100.

CHANGES SINCE LAST ISSUE:

AUSTRALIAN MADE



AUSTRALIAN OWNED

"This information is based on data believed by WP Crowhurst Pty Ltd to be accurate at the time of writing but is subject to change without notice. It is given in good faith, for the assistance of users and is of a general nature. No legal warranty expressed or implied is made as to its accuracy, completeness or otherwise. Every person dealing with the materials referred to herein does so at their own risk absolutely and must make independent determinations of suitability and completeness from all sources to ensure their proper use. We have no control over the conditions under which these products are stored, handled or used and therefore our recommendations must not be regarded as amounting to legal warranty or as involving any liability on us". ©

Research Laboratory Accredited by the National Association of Testing Authorities Australia Reg. Lab No. 931

