

SOLVER LINE 4603 - CENTRE-LINE MARKING PAINT**DESCRIPTION:**

Solver Centre-line Marking Paint is especially designed for line marking on surfaces wherever quick drying surface markings are required. Formulated to give high wear resistance, maximum reflection and excellent durability when exposed to the weather.

USE ON:

Roads, pedestrian crossings, parking areas, air fields, tennis courts, factory floors, etc.

DO NOT use for any purpose other than as specified in our literature.

COVERAGE:

1 litre will cover approximately 26 metres of a line 100 millimetres wide, on a smooth surface when applied at our recommended wet film thickness of 375 micrometers.

SURFACE PREPARATION:

All surfaces to be painted must be thoroughly dry and free from dirt, etc. Grease and oils should be completely removed. Do not paint over soft bitumen. Allow newly laid bitumen surfaces to harden properly, and new concrete to cure fully, before painting.

STIRRING:

Mix contents thoroughly with a broad flat paddle reaching to the bottom of the can. Avoid storing the container in the direct sun.

THINNING:

Thin only if necessary to achieve sufficient atomisation, with SOLVER Line 4600 Spraying (Fast) Thinner. Do not thin more than 10% as film build and hence durability will be reduced.

APPLICATION:

Normally applied by airless or conventional spray. However, small areas can be brushed.

For maximum durability apply at the film thickness recommended under coverage. Adjust tip sizes for width and distance from the surface to achieve the desired result.

DRYING TIME:

When the temperature is around 25°C:-

DRY TO TOUCH	:	2- 3 mins.
RECOAT	:	10 mins.
DRY TO HANDLE	:	8-10 mins.

Will take traffic after 8-10 minutes drying under normal summer drying conditions when applied at the recommended film build. Very heavy applications will naturally take longer to dry.

CLEAN UP:

Clean equipment with SOLVER Line 4600 Spraying (Fast) Thinner.

COLOURS:

White, Yellow (Lead Free) & Black.

SIZES:

20 litre, 4 litre.
(Black available in 4 litre only)

CAUTION:

Highly Flammable.

PROVIDE ADEQUATE VENTILATION DURING USE

KEEP OUT OF REACH OF CHILDREN

FOR FURTHER SAFETY INFORMATION REFER TO MATERIAL SAFETY DATA SHEET OVERLEAF AND PRODUCT INFORMATION SHEET SS-100.

CHANGES SINCE LAST ISSUE: