

Duraguard®



So tough, we've given it a 15 Warranty

Solver Duraguard is an ultra premium exterior acrylic, packed with Solver technology.

Duraguard offers a range of self priming water-based coatings, formulated to provide outstanding durability. Incorporating a combination of flexible polymers and ultra violet absorbers for the ultimate weather protection, Duraguard also contains powerful anti-fungus agents to inhibit mould and fungal growth.

Presented in new fresh labels, Duraguard is the same product you have come to love and rely upon to protect your exterior surfaces. Available in four sheen levels – Matt, Low Sheen, Satin and Gloss, there's a product to suit every application.

Duraguard's advanced technology means that we can now offer a 15 year Warranty against, flaking, peeling or blistering.

The Performance Warranty:

Duraguard, if applied correctly on sound, properly prepared surfaces in accordance with label instructions, will not flake, peel or blister for 10 or 15 years depending on number of coats and surface type as shown in the table below. If this paint fails to perform as specified above, Solver Paints will provide, free of charge, sufficient paint to recoat the affected areas. Paint failure caused by any breakdown of a previous coating is not covered by this warranty. For full details on the warranty refer to www.solverpaints.com.au

Surface type	10 year warranty finish coats	15 year warranty finish coats
Previously painted surfaces	2 coats of Duraguard	2 coats of Duraguard
Bare Timber	2 coats of Duraguard	3 coats of Duraguard
Bare Cement Render, Brick, Fibre Cement, Masonry	2 coats of Duraguard	3 coats of Duraguard
Zincalume®	1 coat of SOLVER Galva-link* & 2 coats of Duraguard	1 coat of SOLVER Galva-link* & 2 coats of Duraguard
Galvanised iron sheet	1 coat of SOLVER Galva-link* & 2 coats of Duraguard	1 coat of SOLVER Galva-link* & 2 coats of Duraguard

* In areas within 1 km of the coast, apply 2 coats of SOLVER Galva-link. Zincalume is a registered trademark of BlueScope Steel Limited

Solver Duraguard meets the benchmark for VOC content as required by the Australian Paint Approval Scheme, resulting in reduced air pollution

Duraguard Range	APAS* Maximum VOC Content	Duraguard Range VOC Content
Duraguard Matt	< 70 g/litre	< 41 g/litre
Duraguard Low Sheen	< 70 g/litre	< 46 g/litre
Duraguard Satin	< 80 g/litre	< 46 g/litre
Duraguard Gloss	< 85 g/litre	< 67 g/litre

* APAS = Australian Paint Approval Scheme

**Want a 15 Year performance warranty against flaking, peeling and blistering?
Problem Solved[®]**